

ARROWTITE ARROWPIPE



NON HALOGEN METALLIC LIQUID TIGHT FLEXIBLE CONDUIT (LSFOH)

Item Number	Nominal Size	Inner Diameter		Outside Diameter		Vinyl Sheath Thickness mm.	Bending Radius mm.	Length of Each Roll m.
		Min mm.	Max mm.	Min mm.	Max mm.			
EFF050	1/2"	15.7	16.3	20.2	20.7	0.5	65	30
EFF075	3/4"	20.7	21.2	25.5	26.1	0.8	75	30
EFF100	1"	26	26.6	31.6	32.2	0.8	100	30
EFF125	1 1/4"	34.7	35.4	40.8	41.5	0.8	125	15
EFF150	1 1/2"	40	40.6	46.6	47.2	1	150	15
EFF200	2"	51.3	51.9	58.1	58.7	1	175	15
EFF250	2 1/2"	62.9	63.3	72.1	73	1	200	10
EFF300	3"	77.9	78.7	87.9	88.9	1.2	225	10
EFF400	4"	101.6	102.6	113.2	114.3	1.2	275	10

: LSFOH : Lowsmoke, flame-retardant, zero halogen

NIKEL PLATED BRASS CONNECTORS IP54

Size	Metric Thread	Park Number	PG Thread	Part Number	NRT Thread	Part Number
1/2"	M16	EF16 / M16	PG10	EF16 / PG11	NPT 18	EF16 / M14
3/4"	M20	EF20 / M20	PG16	EF20 / PG16	NPT 14	EF20 / M18
1"	M25	EF25 / M25	PG21	EF25 / PG21	NPT 14	EF25 / M23
1 1/4"	M32	EF32 / M32	PG29	EF32 / PG29	NPT 11 1/2	EF32 / M29
1 1/2"	M40	EF40 / M40	PG36	EF40 / PG36	NPT 11 1/2	EF40 / M38
2"	M50	EF50 / M50	PG42	EF50 / PG42	NPT 11 1/2	EF50 / M44
2 1/2"	M63	EF63 / M63	PG48	EF63 / PG48	NPT 11 1/2	EF63 / M56
3"	M75	EF75 / M75	-	-	-	-
4"	M100	EF100 / M100	-	-	-	-

: Other type of connector are available (made to order)